Application No.: 10/030,237 Docket No.: HCM-019USRCE

AMENDMENTS TO THE CLAIMS

Please amend Claims 1 and 17 as shown below.

1. (Currently Amended) Apparatus for deriving energy from waves, the apparatus comprising

a chamber adapted to float in water but having a water plane area such that its vertical

oscillating movement is substantially damped relative to the height of waves in the water in

which it is floating,

a chamber inlet port at one end of the chamber adapted to face into a wavetrain,

a baffle in the chamber, and

a manifold located in the chamber opposite the chamber inlet port,

a baffle located in the chamber opposite the chamber inlet port to receive the water

exiting the manifold, and

vertical side walls in the chamber delivering compressed air to a the manifold and thence

to an outlet port and the baffle.

2. (Previously Presented) Apparatus as claimed in claim 1, in which, in use, waves

travel through the inlet port and compress air in the wave troughs as each wave advances into the

manifold and then hits the baffle whereby the compressed air is forced out of the outlet port to

provide a source of energy.

3. (Previously Presented) Apparatus as claimed in claim 1, in which the chamber is

an elongate chamber.

2

Application No.: 10/030,237 Docket No.: HCM-019USRCE

4. (Previously Presented) Apparatus as claimed in claim 1, in which the chamber is formed from the side walls spaced apart by a top plate.

- 5. (Original) Apparatus as claimed in claim 4, in which one end of the side walls is joined by an end wall and the other end of the side walls are spaced to provide the inlet port.
- 6. (Original) Apparatus as claimed in claim 5, in which a bottom plate spans the side walls and the side walls provide at least part of the buoyancy for the chamber.
- 7. (Previously Presented) Apparatus as claimed in claim 5, in which the baffle is provided adjacent the end wall.
- 8. (Previously Presented) Apparatus as claimed in claim 1, in which the baffle tapers towards the inlet port.
- 9. (Previously Presented) Apparatus as claimed in claim 1, in which the chamber includes a pair of tapering side plates adjacent each side wall to compress the air entering in successive wave troughs.
- 10. (Original) Apparatus as claimed in claim 9, in which the angle of taper of the side plates is adjustable.
- 11. (Previously Presented) Apparatus as claimed in claim 1, in which an internal ramp is provided between the inlet port and the manifold.

Application No.: 10/030,237 Docket No.: HCM-019USRCE

12. (Original) Apparatus as claimed in claim 11, in which the angle of the ramp is adjustable.

- 13. (Previously Presented) Apparatus as claimed in claim 1, in which the air outlet port leads off the manifold adjacent the baffle.
- 14. (Previously Presented) Apparatus as claimed in claim 1, in which a wave water outlet is provided in the chamber adjacent the baffle.
- 15. (Previously Presented) Apparatus as claimed in claim 1, in which means are provided to adjust the buoyancy of the chamber to adjust its height in the water to suit different wave conditions.
 - 16. (Cancelled)
- 17. (Currently Amended) Apparatus for deriving energy from waves, the apparatus comprising

a chamber adapted to float in water but having a water plane area such that its vertical oscillating movement is substantially damped relative to the height of waves in the water in which it is floating,

a chamber inlet port at one end of the chamber adapted to face into a wavetrain, a manifold in the chamber at the end of the chamber remote from the inlet port, an outlet port in the manifold,

a baffle in the manifold, and

Application No.: 10/030,237 Docket No.: HCM-019USRCE

vertical side plates <u>in the chamber</u> whereby waves advancing horizontally through the chamber are induced to compress air in their troughs and deliver compressed air to the manifold and thence to the manifold outlet port.